



ACC102-01	Manifold 4xDN8
ACC102-02	Manifold 3xDN8 + 1xDN20
ACC102-03	Manifold 4xDN20
ACC102-04	Manifold 4xDN20 + 1xDN8
ACC102-05	Manifold 1xDN40+3xDN20

DESCRIPTION

- Recover and Refill gas from/to several compartments simultaneously saving time
- Available in **different versions** to meet all compartments' needs



TECHNICAL SPECIFICATIONS

DIMENSIONS: Length: 500 mm - Width: 360 mm - Height: 120 mm

🕸 WEIGHT: 14 kg

COLOURS: Yellow: RAL1016; Black: RAL9005

Synecom SRL Via Circonvallazione Ovest, 27 - Stezzano (BG) - ITALIA





synecomsf6.com





STANDARD EQUIPMENT

N° 3 ball valves

- N° 4 DN20 coupling valve
- N° 1 DN8 coupling valve

OPTIONAL ACCESSORIES

- ☆ TBS101-02: 2mt Rubber hose DN8 with DN8 female coupling valves
- ☆ **TBS101-03**: 5mt Rubber hose DN8 with DN8 female coupling valves
- ☆ TBS101-04: 10mt Rubber hose DN8 with DN8 female coupling valves
- ☆ VAL102-01: Adapters kit DN8
- ☆ TBS102-01: 5mt Rubber hose DN20 with DN8 female valves
- ☆ TBS102-02: 10mt Rubber hose DN20 with DN20 female valves
- ☆ TBS102-03: 20mt Rubber hose DN20 with DN20 female valves
- ☆ VAL103-01: Adapters kit DN20

CERTIFICATES ISSUED

Plant Leak Test Certificate (performed by qualified technicians UNI EN ISO 9712 - SNT TC1A)

PROVIDED DOCUMENTS

Operating Manual

SF₆ safety data sheet

Synecom SRL Via Circonvallazione Ovest, 27 - Stezzano (BG) - ITALIA





synecomsf6.com